# For steep passages with slopes above 6% grade

Young cattle Calves Fattening cattle Dairy cattle



### For steep passages

MONTA is specially designed for steep walkways. Beside helping to support the hoof, the V-shaped rib profile also promotes the drainage of liquids. Further, the square imprinting between the ribs boosts grip. In practice, the mat has proven its effectiveness on slopes up to 15% grade. It can be navigated in either direction. It is ideal for use on stationary, concrete loading ramps for transporting animals to and from the barn.



- For slopes above 6% grade
- V-shaped rib profile supports hooves
- Compatible with vehicle traffic, e.g. farm yard loader or tractor, up to a max. 10% slope

#### **Technical data**

Dimensions (mm / cm)	Thickness	Width	Length
MONTA	24 mm	65 / 130 cm	200 cm

Dimensions (in / ft)	Thickness	Width	Length
MONTA	1"	25 ¼ / 51 ¼"	78 3/4"

# **Application area**

Steep passages with slopes above 6% grade

# **MONTA**

# For steep passages with slopes above 6% grade



Young cattle Calves Fattening cattle Dairy cattle

#### **Application area**

Also for stationary, concrete loading ramps for transporting animals to and from the barn

In practice, tested on slopes up to 15% grade

### Installation and fixing

Single mats are very easy to handle <u>Installation instructions</u>

Min. 9 fixings / narrow mat or 10 fixings / wide mat

KRAIBURG fixing system: Stable and secure, rounded and countersunk

### Compatibility with vehicle traffic

**MONTA** is compatible with vehicle traffic, e.g. farm yard loader or tractor, up to a max. 10% slope With authorized pneumatic tires for recommended inflation pressure up to max. 4 bar. <u>Vehicle traffic specifications</u>

Protect mat edges at the start and end of the mat surface.

#### Note:

Max. half walking speed (approx. 2 km/h)

Drive straight ahead only / do not steer any radius

Do not accelerate or brake on the mat

### Cleaning and maintenance

**Keep mats as clean as possible.** Essential for hoof health and slip resistance!

Treatment with a high-pressure cleaner and standard cleaning agents possible.

#### **Tolerances**

Thickness: +3/-2 mm

Width + length: +/- 1.5% (DIN ISO 3302-1 tolerance class M4)

Please refer to the relevant KRAIBURG specifications and installation instructions, which provide valuable hints and tips.

The products featured here are exclusively intended for the demonstrated applications. Technical details subject to change. Our General Terms and Conditions apply. Legal basis is the German version of the document.

# **MONTA**

# For steep passages with slopes above 6% grade



Young cattle Calves Fattening cattle Dairy cattle

**Note on imperial measurements:** Our products are manufactured according to metric specifications. The imperial measurements are therefore only intended as a guide. Inaccuracies may occur due to conversion and rounding.