


Universal basic comfort

KARERA P meets the basic requirements of an animal-friendly walking area mat: it provides better sure-footedness, is pleasantly soft and easy to clean. It is ideal for all paved walking areas in barns – both for walking alleys with a manure removal system and all paved areas without stationary or mobile manure removal, such as milking parlors, collecting yards or crossing passages. Easy-to-use single mats featuring our proven puzzle interlock system facilitate installation. At the same time, the puzzle interlock system compensates for the natural thermal expansion of the rubber – resulting in virtually jointless floor areas.



- **Wide range of dimensions:**
Accurately fitting width in 5-cm increments
- **In principle, suitable for all scraper models and robot collectors and compatible with vehicle traffic**
- **Faster milking due to improved parlor entrance and relaxed cows**



Technical data

Dimensions (mm / cm)	Thickness	Width	Length
2-sided puzzle	21 mm	95-130 cm in 5-cm increments	170 cm
		(Puzzle interlock system wide sides)	
3-sided puzzle	21 mm	37.5 / 47.5 / 52.5 / 57.5 / 62.5/ 92.5 / 97.5 / 102.5 / 107.5 / 117.5 / 122.5 / 127.5 cm	170 cm

KARERA P

21 mm thick - basic comfort for all paved walking areas



legt die Weide in den Stall

Young cattle Calves Fattening cattle Dairy cattle

Dimensions (mm / cm)	Thickness	Width	Length
(Puzzle interlock system wide sides and on one longitudinal side)			
4-sided puzzle	21 mm	125 cm	170 cm

Dimensions (in / ft)	Thickness	Width	Length
2-sided puzzle	$\frac{7}{8}$ "	37 $\frac{3}{8}$ -51 $\frac{1}{4}$ " in 2" increments	67"
(Puzzle interlock system wide sides)			
3-sided puzzle	$\frac{7}{8}$ "	14 $\frac{3}{4}$ / 18 $\frac{3}{4}$ / 20 $\frac{5}{8}$ / 22 $\frac{5}{8}$ / 24 $\frac{3}{8}$ / 36 $\frac{3}{8}$ / 38 $\frac{3}{8}$ / 40 $\frac{3}{8}$ / 42 $\frac{3}{8}$ / 46 $\frac{1}{4}$ / 48 $\frac{1}{4}$ / 50 $\frac{1}{4}$ "	67"
(Puzzle interlock system wide sides and on one longitudinal side)			
4-sided puzzle	$\frac{7}{8}$ "	49 $\frac{1}{4}$ "	67"

Application area
All paved walking areas with and without a manure removal system
Walking areas for beef cattle

Slope
Up to max. 3%

Installation and fixing
Single mats are very easy to handle. Installation instructions
Prefabricated fixing points facilitate installation.
KRAIBURG fixing system: Stable and secure, rounded and countersunk

Compatibility with vehicle traffic
KARERA P is compatible with vehicle traffic, e.g. farm yard loader or tractor with authorized pneumatic tires for recommended inflation pressure up to max. 4 bar.

Compatibility with vehicle traffic

(Note: Drive with the necessary caution and ensure adequately large turning radii!)

[Vehicle traffic specifications](#)

Manure removal

In principle, we recommend the use of scraper facilities that are specially designed for rubber flooring. In the case of conversions, always adapt the scraper facility in consultation with the scraper manufacturer in strict accordance with the KRAIBURG guidelines for manure scrapers.

[Guidelines for manure scrapers](#)

Robot collectors must be suitable for use on rubber flooring.

Important: Check scrapers at least once a year and grind any sharp edges round!
Use robot collectors according to the specifications and check them regularly!

Maintenance tip

Keep flooring on walking areas and in milking areas as clean as possible Essential for hoof health and slip resistance!

Treatment with a high-pressure cleaner and standard cleaning agents possible.

[Guidelines for cleaning milking parlor mats](#)

KRAIBURG warranty

5 years

Detailed information on our warranty (with consideration of the service life) is available upon request from your contractual partner / dealer.

Tolerances

Thickness: +3/-2 mm

Width + length: +/- 1.5% (DIN ISO 3302-1 tolerance class M4)

Please refer to the relevant KRAIBURG specifications and installation instructions, which provide valuable hints and tips.

The products featured here are exclusively intended for the demonstrated applications. Technical details subject to change. Our General Terms and Conditions apply. Legal basis is the German version of the document.

Note on imperial measurements: Our products are manufactured according to metric specifications. The imperial measurements are therefore only intended as a guide. Inaccuracies may occur due to conversion and rounding.